Department of Labor and Industries Factory Assembled Structures PO Box 44430 Olympia WA 98504-4430



LOW VOLTAGE FIRE/INTRUSION ALARM CHECKLIST

This checklist is designed to be generic in content and may not include all requirements for your particular installation. Manufacturer's installation instruction must be adhered to <u>and available to the inspector at the time of the inspection</u>

<u>REFERENCE</u>		COMPLIANCE Was No	
WAC 296-150M	Alteration permit purchased and insignia issued.	Yes	No
RCW 18.27.200	Contractor doing work is registered.		
HUD 3280.305	No holes bored in floor joist within 2" of top or bottom		
HUD 3280.307d	Exterior surfaces shall be sealed to resist the entrance of rodents.		
HUD 3280.903	Protection from transportation shock and vibration.		
NEC 110-36	All equipment shall be installed per specs.		
NEC 725-9	Equipment to be bonded to frame. Bonding at frame to include a star washer		
NEC 725-6	All installations shall be in a workmanship-like manner.		
NEC 725-8(b)	Conductors shall be protected from physical damage.		
NEC 725-41	Installation for a Class 2 circuit.		
NEC 725-51	Circuit breaker for the transformer to be sized per manufacturer's instructions.		
WAC 296-150M	Re-inspection fee charged if applicable		
Comments:			

NOTE: UNLESS OTHERWISE SPECIFIED IN CODE, THE MANUFACTURER'S INSTALLATION INSTRUCTIONS MUST BE FOLLOWED.